

GRAPHICLITE D5000 VIEWING SYSTEMS FOR CRITICAL SOFT PROOFING

Accurate ISO-Compliant D50 Standard Viewing and Soft Proofing Environment



Model EVS-3552/SP can accommodate one or two 30"/76cm LCD monitors

Soft Proofing

New technology has made it possible to implement remote and soft proofing. Critical to the success of accurate soft proofing is the viewing environment. GTI® is the premier supplier of viewing systems designed to assure consistent color appearance throughout the reproduction process and to help you implement successful soft proofing.

We offer soft proofing viewing systems from desktop to the pressroom which are specially designed to provide precise and convenient color viewing conditions to compare hard copy to proofs on a monitor.

Advantages of Soft Proofing

You may still find it necessary to produce a hard proof, however, soft proofs that can be viewed on a computer monitor and easily shared with those in the production process provide money- and time-saving benefits which include:

- Allowing more personnel involved in the production and color approval of a job to assist with image and text changes and with the review of the latest copy of a proof
- Making last-minute changes readily
- Reducing the cost of materials
- Decreasing the cost and the time involved in transporting hard proofs to those involved in the job approval process
- Getting jobs to press faster

The EVS/SP viewing systems are designed to provide consistent and accurate ISO standard viewing conditions in addition to the ideal viewing environment to evaluate accurate soft proofs. The digital intensity control allows precise matching of the luminance of the color monitor for accu-

rate soft proofing and includes a by-pass switch to easily change to full intensity for hard copy comparisons (while the soft proofing intensity setting is maintained).

Single or dual LCD monitors (not included) can easily be positioned for optimal viewing since each mounting arm allows full swivel, tilt or pull-out (for calibration) adjustability of the monitor. The LiteGuard® II viewing system monitor (which indicates when the unit is warming up and when the lamps require changing) is included with the EVS/SP models.

Features

- ISO 3664 standard viewing conditions
- Digital dimming for precise intensity control
- LiteGuard II viewing system monitor
- Viewing area 29x52"/74x132cm
- Air filters for CPU cabinet
- Monitors are mounted in the center of the rear wall.
- Single or dual LCD monitor support
- Easy-to-move models on included floor casters
- Convenient pull-out keyboard tray
- Sidewalls to block ambient light

Model	Description	Packed Weight
EVS-3552/SP	Includes cabinet with casters Physical Dimensions: 85 x 54 x 36"/216 x 137 x 91cm	550 Lbs./250 Kg.
EVS-3552/SP/FD	Includes 8 flat file drawers (50.5 x 28.25 x 2"/128 x 71 x 5cm) instead of casters Physical Dimensions: 85 x 54 x 36"/216 x 137 x 91cm	755 Lbs./342 Kg.
EVS-1/SP	Includes cabinet (optional casters available) Physical Dimensions: 85x54x31"/216x137x79cm	430 Lbs./195 Kg.
For operation at 100, 120 or 230V/168 watts		