

# SINGLE AND MULTISOURCE LUMINAIRES FOR INDUSTRIAL APPLICATIONS

*These color viewing luminaires provide the precise color quality specified by ATSM D1729-96 for critical color comparisons.*

## Features

- Aluminized reflectors for maximum output and neutral color rendition
- UV-transmitting, optically clear, prismatic lens
- Electronic lamp ballasts for dependable, flicker-free operation
- Operation on a range of input voltage (120-240V)
- Meet the ATSM D1729-96 standard for critical color comparisons



## CMIite Lamps

GTI® lamps are manufactured with a unique blend of fluorescent phosphors. Unequaled by similar lamps in the industry, the CMIite® lamps produce a true full-spectrum white light which renders colors with the highest degree of accuracy and efficiency. In GTI equipment,

the CMIite color viewing lamp produces an actual system CRI approaching 95.



## GLL-e Series

GLL-e luminaires are designed to be installed on switched electrical circuits so neither switches nor line cords are included with them (however a line cord is available as an option at an additional cost for each light source).

**GLL-432e** Luminaire with a single light source (your choice of D65, D75 or D50) with four 48"/122cm T8 lamps.

**GLL-DSe** Dual light source luminaire that consists of four 48"/122cm D50 T8 lamps and four 48"/122cm D65 T8 lamps.

**GLL-DS/40e** Dual light source luminaire that consists of five 60"/152cm D50 T8 lamps and five 60"/152cm D65 T8 lamps.

**GLL-M3/32e** Luminaire with three light sources (D65; CWF or TL84; incandescent 2856K). This system includes four 48"/122cm D65 T8 lamps, three 48"/122cm CWF (or TL84) T8 lamps and six incandescent 2856K lamps. Other light sources such as D50, D75, U30 (ADV30), SPX35 and TL83 are available upon request.

## GLE Unit

The GLE multisource luminaire is supplied with a line cord and front-mounted control switches. It can be supplied with a ColorGuard® II light monitoring system which displays the lamp hours used, lamp hours remaining and warm-up time, and which also provides a warning in advance when relamping is needed.

**GLE-DS** Dual light source luminaire that consists of five 48"/122cm D50 T8 lamps and five 48"/122cm D65 T8 lamps.

Model	Dimensions	Watts	Packed Weight	Lamps
GLL-432e	5.75 x 48.75 x 23.75"/15 x 124 x 60cm	168	45 Lbs./21 Kgs.	Set of 4 (L432)
GLL-DSe	5.75 x 48.75 x 23.75"/15 x 124 x 60cm	210	63 Lbs./29 Kgs.	Set of 8 (L832/DS)
GLL-DS/40e	5.75 x 60.75 x 23.75"/15 x 154 x 60cm	270	50 Lbs./23 Kgs.	Set of 10 (L1040/DS)
GLL-M3/32e	3.5 x 52 x 30"/9 x 132 x 76cm	410	60 Lbs./27 Kgs.	Set of 13 (LM3/32)
GLE-DS	5.75 x 48.75 x 23.75"/15 x 124 x 60cm	270	50 Lbs./23 Kgs.	Set of 10 (L1032/DS)

Brand and product names are trademarks of their respective holders. All trademarks may be registered in the U.S.A. and/or other countries. Product design and specifications subject to change without prior notice.

Los productos están protegidos por patentes y patentes pendientes en los EE.UU. y el extranjero, y son marcas registradas y propiedad de sus fabricantes. Las especificaciones y el diseño están sujetos a cambio sin previo aviso.